

Safety Cage

The WPA-N Safety Work platform has been designed for safe elevating of personnel in the workplace.

Features include:

- Standard model zinc coated finish
- Designed to carry 2 persons (250Kg max)
- Supplied as flat pack for easy storage and transport
- Designed to comply with AS 3990:1993 under the design loads of AS 2359.1:1995
- Retaining attachment pin



Inward opening, self closing door

Toe boards on sides with skid resistant floor plate



Mesh safety screen

Internal handrail

Full length fork pockets

Distance between centre fork pockets

Specifications:

Model	Capacity	Length	Width	Overall height	Fork pocket size	Fork pocket centres
	Kg	mm	mm	mm	mm	mm
WPA-N	250	1090	1155	2070	160 x 60	640
WPA-N (NZ)*	250	1090	1145	2070	160 x 60	640

*Welded Construction (Not Flatpack) and Hot Dip Galvanised Finish

General Purpose Harness

Features include:

- CONFORMS TO: EN 361 EN 1497 AS/NZ 1891
- General purpose harness with front and rear 'D' attachment points
- Fully adjustable with quick release buckles
- Suitable for; General trades person, construction workers, roofing, vertical climbing, access equipment



Z-35

Z-32

Specifications:

Model	Size	Weight
		Grams
Z-35	M - XL	1460
Z-32	M - XL	1315

Lanyard

Heavy duty polyamide, adjustable rope lanyard with carabiners. Energy absorbing & work positioning.

- CONFORMS TO: EN 355

Specifications:

Model	Max length
	m
ABM-RL	2
ABM-TX3	2



ABM-RL



ABM-TX3